

MATERIAL SAFETY DATA SHEET
TRACE CHEMICALS LLC

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME.....:FOAM EATER AEROSOL
PRODUCT CODE.....:FEA-1
CHEMICAL FAMILY.....:Mixture
CHEMICAL NAME.....:Aerosol formulation of
dimethylpolysiloxane
FORMULA.....:Mixture

MANUFACTURER: TRACE CHEMICALS LLC
2320 LAKECREST DRIVE.
PEKIN, IL 61554
(309)347-2184
EMERGENCY TELEPHONE NO:
CHEMTREC: (800)424-9300 (Toll free – U.S.)
(703)527-3887 (Domestic and International)
TRACE : (309)347-2184

2. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

INGREDIENT NAME <u>/CAS NUMBER</u>	<u>%</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OTHER</u>
Perchloroethylene(127-18-4)	64.6	100 ppm	50 ppm	200 ppm (STEL)
Methylated Silica(67762-90-7)	1.0	N/E	N/E	N/E
Propane(74-98-6)	11.0	1000 ppm	Asphixiant	N/E
Butane(106-97-8)	11.0	800 ppm	800 ppm	N/E

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EFFECTS OF ACUTE OVEREXPOSURE: Eye irritant, skin irritant. Narcotic in high concentrations.

EFFECTS OF CHRONIC OVEREXPOSURE: Liver and Kidney disease. Skin irritation and dermatitis.

continued on next page

4. FIRST AID MEASURES

IF ON SKIN: Wipe off with a towel. Wash affected areas with soap and water. Get medical attention if irritation persists.

IF IN EYES: Flush eyes with large amounts of water for at least 15 minutes.

Seek medical attention.

IF SWALLOWED: Consult physician-do not induce vomiting. If conditions remain, get medical attention.

IF INHALED: Remove victim to fresh air. If breathing difficulty is encountered, administer oxygen if indicated. May apply artificial respiration if breathing has stopped. Get medical attention.

5. FIRE FIGHTING MEASURES

FLASH POINT.....:156°F.

EXTINGUISHING MEDIA.....:Dry chemicals, CO2, water fog, foam, alcohol foam.

SPECIAL FIRE FIGHTING PROCEDURES.....:Keep containers cool. Use equipment or shielding to protect personnel from bursting or venting containers. Wear goggles and self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES:

SPILL OR LEAK PROCEDURES.....:Avoid breathing vapors, remove ignition sources, clean up spill with absorbant materials(saw dust, clay) and ventilate area. Dike area to contain spill. Place in closed containers for disposal.

7. HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS.....:Do not puncture or incinerate can. Do not store near flame or at temperatures above 120°F. Corrosive action on metals, plastics, rubber, etc. – None.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION REQUIREMENTS...:Goggles or safety-glasses with splash guards.

SKIN PROTECTION REQUIREMENTS.....:Solvent resistant gloves required for Prolonged or repeated contact.

RESPIRATORY/VENTILATION REQUIREMENTS.....:Provide local exhaust if used in a confined area .

EXPOSURE LIMITS.....:Not established for product as whole. Refer to Section 2.

continued on next page

